

# DIGITAL RPM METER

## MODEL: 250



### FEATURES

Optical RPM Measurement.  
MAX/MIN/AVG and HOLD functions.  
Auto-power off.  
Backlight function.  
Self-adhesive reflective tape.  
Protective cap for safe storage.  
Attached with carrying strap.

**Storage temperature:** -20°C to 60°C, 0 to 80% R.H. with battery removed from meter.

**Low battery indication:** The “ ” is displayed when the battery voltage drops below the operating level.

**Battery:** 1.5Vx2pcs AAA size.

**Dimensions:** 24.7mm(T)x50.9mm(W)x 132.9mm(H).

**Weight:** Approx. 110g including batteries.

### SPECIFICATION

**Operating environment:** 0°C to 50°C at <70% R.H.

**Measuring range:** 100.0 to 99999 rpm

**Resolution:**

0.1 rpm(100.0 to 19999.9 rpm)

1 rpm(20000 to 99999 rpm)

**Accuracy:** Stated accuracy at 23°C±5°C, <75% R.H.

±0.02% of reading + 1dgt

**Units:** rpm, rps

**Measurement rate:** 1 time/second.

**Temperature Coefficient:** 0.1 times the applicable accuracy specification per °C out of 18°C to 28°C(64°F to 82°F).

## Made in Taiwan