

SOUND LEVEL METER MS6701

MS6700

- LCD digital display
- Analog bar indicator
- Wide dynamic range
- Auto/Manual range
- Fast/Slow response selectable
- MAX value hold function
- A/C weighting selection
- Date and time display
- AC/DC auxiliary output
- Back light
- Low power indication

Specifications

Measurement range	30dB ~ 130dB
Accuracy	±2dB
Resolution	0.1dB
Display	3 1/2 digitals
Sample rate	2 times/s
Frequency range	30Hz ~ 8kHz
Over range indication	"UNDER" or "OVER"
Low power indication	
Auxiliary output	AC 0.707Vrms at full range for each level, impedance 600Ω DC 10mV/dB, impedance 100Ω
Battery voltage	6 x 1.5V (AAA)



MS6701

- LCD digital display
- Analog bar indicator
- Wide dynamic range
- Auto/Manual range
- Fast/Slow response selectable
- MAX value hold function
- A/C weighting selection
- Date and time display
- AC/DC auxiliary output
- Memory function
- RC232C interface
- Computer record graph software
- Back light
- Low power indication

Specifications

Measurement range	30dB ~ 130dB
Accuracy	±2dB
Resolution	0.1dB
Display	3 1/2 digitals
Sample rate	2 times/s
Frequency range	30Hz ~ 8kHz
Memory function	16000 records
Over range indication	"UNDER" or "OVER"
Low power indication	
Auxiliary output	AC 0.707Vrms at full range for each level, impedance 600Ω DC 10mV/dB, impedance 100Ω
Battery voltage	6 x 1.5V (AAA)

