



## GENERAL POLYTRONIC SYSTEMS LTD.

### GPS-5030EC

Earth Continuity Tester

#### • Features:

- Clear and concise display on high-brightness VFD
- The invariable current
- Timing test function from 0.5s to 999s randomly set
- Judge via comparing the windows
- Touch inspection function
- RS-232C, REMOTE, and status output interface to make operation convenient
- Memory backup function





## GPS-5030EC

Earth Continuity Tester

Specifications	
Model	GPS-5030EC
Test Current	3~30A
Resistance Value	0~1.2 $\Omega$
Max. Output Power	150VA
Output Voltage	0-5.5V
Test time	0.5~999s
Resistance Display Accuracy	$\pm 5\% + 20 \mu\Omega$
Current Display Accuracy	$\pm 5\%$
Remote Control	START, STOP, STARTENABLE, HV ON Display
Signal Input&Output Interface	<b>Status Output:</b> Pass, U-FALL, PROTECTION, READY, TEST, HV-ON <b>Control:</b> START, STOP, ENABLE, INTERLOCK
Communication Interface	RS232
Power supply	220V $\pm 10\%$

• General Polytronic Systems Ltd  
14 Regents St. London, NW10 5LG, UK  
Tel: +44 20 8964 3600  
Email: sales@gpslimited.com  
Web: www.gpslimited.com